

D6.7 - Reduced DSSCK

Document Author(s)Côme BERGER (TAS-F)

Document Contributor(s) Stéphanie BEHAR-LAFENETRE (TAS-F)

Abstract

This document constitutes the Design and Development Specification for the satellite Construction Kit (DSSCK) applicable to the ORUs (Orbital Replacement Unit) in the frame of ORU BOAS project.

Keywords

ORU-BOAS, DSSCK



Information Table

Contract Number	101082078
Project Acronym	ORU-BOAS
Project Title	ORU BASED ON BUILDING BLOCKS FOR ADVANCED ASSEMBLY OF SPACE SYSTEMS
Topic	HORIZON-CL4-2021-SPACE-01-12
Type of Action	HORIZON Research and Innovation Actions
Start date of project	1 January 2023
Duration	24 months
Project Coordinator	SENER
Deliverable Number	D6.7
TASF internal reference	0005-0018915022
Deliverable Title	Reduced DSSCK
Version	01
Status	Final
Responsible Partner (organization)	TAS-F
Deliverable Type	Document/Report
Contractual Date of Delivery	December 2024
Actual Date of Delivery	27 th December 2024
Dissemination Level	PU - Public



Authoring & Approval

Prepared by					
Name and Organization	Position and title	Date			
Côme BERGER	BERGER TASF - Satellite Systems Engineer				

Reviewed by						
Name and Organization	Position and title	Date				
Stéphanie BEHAR-LAFENETRE	TASF - EROSS IOD Coordinator	20.12.2024				

Approved for submission by								
Name and Organization	Organization Position and title Date							
Javier Vinals	ORU-BOAS Project Manager	20.12.2024						

Document History

Version	Date	Status	Author	Description
01	20.12.2024	Final	Côme BERGER	Initial release

Disclaimer

Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or HaDEA. Neither the European Union nor the granting authority can be held responsible for them.

Copyright © 2022, ORU-BOAS Consortium, All Rights Reserved.

This document and its content are the property of the ORU-BOAS Consortium. It may contain information subject to intellectual property rights. No intellectual property rights are granted by the delivery of this document or the disclosure of its content. Reproduction or circulation of this document to any third party is prohibited without the prior written consent of the Author(s), in compliance with the general and specific provisions stipulated in ORU-BOAS Grant Agreement and Consortium Agreement.

THIS DOCUMENT IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS DOCUMENT, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Table of Contents

1. Intr	oduction	8
1.1	Scope and Purpose	8
1.2	List of acronyms	8
1.3	Definitions	9
1.4	Applicable & Reference Documents	10
1.4	.1 Applicable Documents	10
2 Ser	vice and Transport Mission	11
2.1	Transporter Performance	11
2.2	Lifetime	11
2.3	Ground Segment & Data Transmission	12
2.4	Launcher Compatibility	12
3 Env	vironmental Conditions	13
3.1	Mechanical environment	13
3.2	Thermal Environment	14
3.3	Radiation	15
4 ORI	U Interfaces	16
4.1	Mechanical	16
4.1	.1 Dimensions	16
4.1	.2 Mass	16
4.1	.3 Handling & Fixation	16
4	I.1.3.1 Standard Interface	16
4	I.1.3.2 HRM	16
4.2	Thermal	17
4.3	Electrical	17
4.3	.1 Power	17
4.3	.2 Pin Allocation	17
4.3	.3 Grounding	17
4.3	.4 Transfer Phase	18
4.4	Command and Control	18
4.5	Pointing	18
4.6	EMC & ESD	18
4.6	.1 EMC	18



	4.6.2	ESD	18
5	Mission I	ntegration and Transportation Service Management	19
	5.1 Intro	oduction	19
	5.2 Tran	nsportation service management	19
	5.2.1	Contract organization	19
	5.2.2	Mission Integration Schedule	20
	5.2.3	Mission Documentation	21
	5.2.4	Integration Phase	22
	5.2.5	Applicable Standards	22

1. Introduction

1.1 Scope and Purpose

This document outlines the Design and Development requirements for any generic ORU (Orbit Replaceable Unit) to be carried in space thanks to a Transporter.

The primary goal of such a document is to specify technical requirements towards any 'ORU Provider' from an 'ORU Transporter' standpoint.

A secondary goal of the document is to derive programmatic essentials (e.g. schedule backbones, preliminary deliverable lists) linked to these technical requirements from the ORU Transporter viewpoint.

It shall be noted that the 'ORU Customer' within this document is only the ORU Transporter (and <u>not</u> the End User of the actual payload, service or function provided by the ORU in space - once installed onto a space systems).

By 'ORU Transporter', it is meant Space Carrier from launcher (rocket) carrier injection to ORU delivery onto a space systems.

Note: As an example, a typical 'ORU Transporter' could be a servicer or a logistic vehicle.

1.2 List of acronyms

CAM	Collision avoidance manoeuvre: a manoeuvre performed by the servicer aiming to place the servicer in an orbit passively free of collision with the servicer, not to be confused with collision avoidance manoeuvre with debris or active satellite -other than dummy client-, or COLA (Collision Avoidance).
MLI	Multi-Layer Insulation
ORU	Orbital Replacement Unit



1.3 Definitions

Orbital Replaceable Unit (ORU): -the object of this specification-, a standalone unit (payload, service or function) designed to be transported by the ORU Transporter towards an orbital space systems which will receive & operate it during the ORU lifetime.

ORU Transporter: Space Carrier from launcher (rocket) carrier injection to ORU delivery onto a space systems. The Transporter does not operate the ORU.

ORU Provider: Supplier of the ORU to the ORU Transporter.

Standard interface: an electromechanical device allowing to mechanically and electrically connect with a matching interface.

TT&C: Telemetry Tracking & Command



1.4 Applicable & Reference Documents

1.4.1 Applicable Documents

[AD1] Space USB Standard Interface Specification, 0005-0018252681, Issue 01



2 Service and Transport Mission

2.1 Transporter Performance

The Transporter Spacecraft or Vehicle shall provide the ORU Transportation service to the ORU Provider under the best possible conditions.

The possible ORU orbit deliveries are described in the table here below:

ORU Orbit Delivery by the Transporter	Feasible	<u>Un</u> feasible
LEO	X	
MEO	X	
GEO	X	
Interplanetary orbits		X

Table 1: ORU Orbit Delivery by the Transporter

Note: Interplanetary missions are deemed unfeasible at this stage as they would require a very specific Transporter spacecraft due to mission constraints (e.g. propulsion subsystems, transfer lifetime). From a business forecast point of view, interplanetary ORU deliveries are not a primary need.

2.2 Lifetime

The Transporter Vehicle will be designed for an ORU Transportation mission of 1 year – maximum.

As a consequence, the ORU Provider shall take this data into account for its ORU design at Kick-Off stage.

During the mission preparation phase, the Transporter shall detail the exact Transportation mission duration and the associated space operation segments (starting from launch and ending with ORU delivery).

Note: This lifetime is consistent with reachable destination orbits specified in Section 2.1.



2.3 Ground Segment & Data Transmission

For any mission, a detailed Ground Segment & TT&C Plan (documentation) will be supplied by the ORU Transporter to the ORU Provider.

The ORU Transporter will be responsible for planning ground segments operations (e.g. ground stations service providers) accordingly, taking into account the ORU technical constraints regarding TT&C.

The ORU Transporter shall detail to the ORU Customer the available ORU Provider TT&C (if available).

The data volumes and protocols will be discussed following Kick-Off.

This topic is mission-specific and shall be co-engineered during the mission preparation phase.

2.4 Launcher Compatibility

The ORU Transporter shall sign the launch contract with a rocket operator of its choice.

These contractual and technical discussions with the launch (rocket) operator shall <u>not</u> be dealt with by the ORU Provider.

This launch contract remains mission-specific in order to offer to the ORU Provider the best choice amongst currently existing (and potentially upcoming) launch providers, both in terms of mission analysis & programmatic (cost & schedule) aspects.

Hence, the launch operator choice is not restricted to specific countries or continents.



3 Environmental Conditions

3.1 Mechanical environment

The mechanical environment due to ORU Transporter is induced by mechanical loads withstood during launch & transportation.

This environment is mission specific and should be discussed from Kick-Off Stage.

The ORU Provider shall ensure & justify that the ORU will not be degraded under such a mechanical environment.



3.2 Thermal Environment

The thermal environment & conditions shall be considered by the ORU Provider when designing an ORU compatible with the transportation mission.

This environment is mission specific and should be discussed from Kick-Off Stage.



3.3 Radiation

The ORU shall be designed by the ORU Provider to withstand radiations during the phase led by the Transporter.

This environment is mission specific and should be discussed from Kick-Off Stage.

A specific radiation analysis shall be performed by the ORU Provider taking into account:

- The Transportation Phase (inputs to be given by the ORU Provider)
- The mission lifetime (inputs to be given by the ORU End User excluded from this document scope)

Given the nature of radiation spectrums and depending on the ORU Orbit Delivery (LEO, MEO, GEO) the Transportation Phase radiation dose may be an (or several) order(s) of magnitude below the mission lifetime radiation dose.

The Transportation Phase radiation spectrum is also highly dependent on the ORU Orbit delivery.

That is why in this document no typical radiation spectrum is specified.



4 ORU INTERFACES

4.1 Mechanical

4.1.1 Dimensions

The ORU from the ORU Provider shall comply with the ORU Transporter available ORU dimensions.

4.1.2 Mass

The ORU from the ORU Provider shall comply with the ORU Transporter own mass categories.

4.1.3 Handling & Fixation

4.1.3.1 Standard Interface

To be able to be mounted onto the Transporter spacecraft and handled post Transportation, the ORU shall be provided along with <u>two passive</u> standard interfaces on two of its external (ORU) sides.

The passive standard interfaces shall comply with [AD1] Space USB EU Standard.

The definition of the mounting location of the ORU onto the Transporter shall be reviewed & agreed by the Transporter.

4.1.3.2 HRM

To withstand mechanical launches, the ORU shall be provide along with a Hold on & Release Mechanism (HRM).

The definition of the supporting HRM shall be reviewed & agreed by the Transporter.



4.2 Thermal

The ORU shall be designed to be thermally decoupled from the Transporter spacecraft.

The ORU shall be designed to receive Sun flux from any direction (including the face of the fixation interface which can be illuminated during robotic transfer).

Active thermal control, if any, shall be autonomous and shall **not** rely on Transporter spacecraft data acquisition/commanding.

The ORU thermal control shall not draw more than the allocated power budget specified in Section 4.3.1.

Any deviation to these Thermal requirements shall be reviewed & agreed by the Transporter before launch.

4.3 Electrical

4.3.1 Power

Power is distributed to the ORU using harness during the Transporter mission.

The ORU Provider shall comply with the ORU Transporter power consumption requirements.

4.3.2 Pin Allocation

The ORU pin allocation shall be compatible of a Standard Interface compliant with [AD1] Space USB EU Standard.

The exact definition of the pin allocation shall be co-engineered before launch, reviewed & agreed by the Transporter.

4.3.3 Grounding

The ORU shall be electrically grounded, i.e. any conductive element shall offer a conductive path to an associated grounding line.

The strategy for ORU grounding shall be proposed by the ORU Provider, providing a grounding sketch at ORU level.

It shall be reviewed & agreed by the ORU Transporter.



4.3.4 Transfer Phase

During the ORU Transfer Phase from the Transporter to the Client, The ORU shall be designed to remain completely unpowered during transfer by the robotic arm for a duration not exceeding 90 minutes.

4.4 Command and Control

The ORU shall be commandable and controllable via a protocol as specified in [AD1] Space USB EU Standard.

4.5 Pointing

Since the ORU Transporter primary goal is not to operate the ORU in space (but to deliver it to a final ORU Client), pointing requirements will not be defined in this document.

If need be, technical discussions can be held between ORU Provider and ORU Transporter on pointing budgets & strategy – before launch.

Any technical need on pointing shall be reviewed & agreed by the Transporter before launch.

4.6 EMC & ESD

4.6.1 EMC

The ORU shall comply with the requirements from ECSS-E-ST-20-07C.

This compliance could be dealt with at Transporter system level – in which case inputs would have to be provided by the ORU Provider to allow a coupled system EMC analysis & validation.

4.6.2 ESD

The ORU shall comply with the requirements from ECSS-E-ST-20-06C.

This compliance could be dealt with at Transporter system level - in which case inputs would have to be provided by the ORU Provider to allow a coupled system charging analysis & validation.



5 MISSION INTEGRATION AND TRANSPORTATION SERVICE MANAGEMENT

5.1 Introduction

To provide the ORU Provider with smooth Transportation preparation, a customer-oriented mission integration and management process is implemented.

The mission integration and management process is consolidated through the mission documentation and revised during formal meetings and reviews.

5.2 Transportation service management

5.2.1 Contract organization

The contractual commitments between the Transporter (or Transport service provider) and the ORU Provider are defined in the following documentation:

- Statement of Work (SoW)
- ORU Technical Specification

The Statement of Work identifies the tasks and deliveries of the parties, and the Technical Specification identifies the technical interfaces and requirements.

At contract signature, a project manager from the Transporter is appointed to be the single point of contact with the ORU Provider. She/He is in charge of all aspects of the mission including technical and financial matters.

Besides the meetings and reviews described hereafter, the Transporter will meet the ORU Provider when required to discuss technical, contractual or management items. The following main principles will apply for these meetings:

- Dates, location and agenda will be defined in advance by mutual agreement.
- The designed host will be responsible for meeting organization.
- The participation will be open for both sides subcontractors and third companies by mutual preliminary agreement.



5.2.2 Mission Integration Schedule

The mission integration schedule will be established in compliance with the milestones and launch date specified in the statement of work.

A typical mission integration schedule is shown here below in Table 3.

Note: Acronyms for reviews are being defined in Section 5.2.3.

		Month before launch												
	-12	-11	-10	-9	-8	-7	-6	-5	-4	-3	-2	-1	0	1
Reviews	КО		ORU-C	DR			ORU-I	RR	ORU-I	RB	FRR		L	IOCR
Procurement Phases														
Mission Analysis														
ORU Integration on Transporter vehicle														
Launch Campaign Preparation														
In-Orbit Commissioning														

Table 2: Mission Integration Schedule – Typic

5.2.3 Mission Documentation

Associated to these reviews and this typical schedule, critical documentation must be reviewed and agreed on both ends (the ORU provider and the Transporter). This ensures a smooth integration of the ORU onto the Transporter vehicle and leads towards a successful launch campaign and in orbit ORU delivery.

Review	Time	ORU Provider	Transporter					
	line	required deliverables	required deliverables					
Kick-Off (KO)	L-12	ORU Mechanical ICD (draft)	Mission plan (draft)					
		ORU Electrical ICD (draft)	Transporter Interface ICD (Mech & Elec)					
			Statement of Work (SoW)					
			ORU Technical Specification					
ORU Critical	L-10	ORU Mechanical ICD	Mission Analysis (Draft)					
Design Review (ORU-CDR)		ORU Electrical ICD	Launch Contract					
(0110 0211)		Mechanical coupled analysis Inputs						
		Electromagnetic and RF compatibility analysis inputs						
		ORU Integration & Test Spec						
		ORU Mechanical & Electrical GSE for Integration on Transporter (Draft)						
ORU Integration	L-6	ORU Mechanical & Electrical	Mechanical coupled analysis Results					
Readiness Review (ORU- IRR)		GSE for Integration on Transporter	Electromagnetic and RF compatibility analysis Results					
nacy			ORU Integration Test Plan					
			ORU Integration Plan					
ORU Integration Review Board (ORU-IRB)	L-4		ORU Integration Test Report					
FRR (Flight	L-2		Mission Analysis					
Readiness Review)			Ground Segment & TT&C Plan					
Launch (L)	L		Mission Status					
In-Orbit Commissioning Review	L+1		Commissioning (ORU Delivery) Report					



5.2.4 Integration Phase

Following a successful ORU-IRR milestone, the Integration Phase will start at the ORU Transporter premises.

It is defined as mechanical & electrical integration of the ORU onto the Transporter spacecraft or vehicle.

This phase will be under the responsibility of the ORU Transporter with technical inputs provided by the ORU Provider as defined in Section 5.2.3 for reviews ORU.

In response, the ORU Transporter will provide Technical Inputs as defined in Section 5.2.3 for reviews ORU-IRR.

This documentation exchange shall be reviewed & agreed by the ORU Transporter which will make final decisions in case of conflict.

Regarding Ground Support Equipments (GSE) necessary to the Integration Phase, they shall be reviewed & agreed by the ORU Transporter.

At this stage, they are mission-specific and no GSE portfolio is available ahead of the project design phases.

5.2.5 Applicable Standards

Any space standard could potentially apply to the ORU mission. This shall be clearly stated at the Kick-Off milestone and indicated contractually in the Statement of Work and Technical Specification.

This document in itself is not a substitute to any broader space standard (e.g. ECSS Standards) that could be called in by the contractual mission-specific documentation.

END OF DOCUMENT

